

## Signage Guide

	TYPE I NONCOMBUSTIBLE	TYPE II NONCOMBUSTIBLE	TYPE III NONCOMBUSTIBLE EXTERIOR WALLS	TYPE IV HEAVY TIMBER	TYPE V ANY MATERIAL PERMITTED BY
FLOOR CONSTRUCTION					
ROOF CONSTRUCTION					
FLOOR & ROOF CONSTRUCTION					

### Required Sign Location(s)

Residential Construction

Affixed to electric meter box attached to the exterior of the structure or affixed to the exterior wall of the residential structure at a point immediately adjacent to the electric box or a location likely to be seen by first responders with approval by the authority having jurisdiction.

The construction type designation shall be "I", "II", "III", "IV" or "V" to indicate the construction classification of the structure under section 602 of the BCNYS

**DESIGNATION FOR STRUCTURAL COMPONENTS THAT ARE OF TRUSS TYPE CONSTRUCTION**

"F"	FLOOR FRAMING, INCLUDING GIRDERS AND BEAMS
"R"	ROOF FRAMING
"FR"	FLOOR AND ROOF FRAMING

Commercial Construction

Exterior building entrance doors, exterior exit discharge doors, and exterior roof access doors to a stairway	Attached to the door, or attached to a sidelight or the face of the building, not more than 12 inches (305 mm) horizontally from the latch side of the door jamb, and not less than 42 inches (1067 mm) nor more than 60 inches (1524 mm) above the adjoining walking surface.
Exterior building entrance doors, exterior exit discharge doors, and exterior roof access doors to a stairway	Attached at each end of the row of doors and at a maximum horizontal distance of 12 feet (3.65M) between signs, and not less than 42 inches (1067 mm) nor more than 60 inches (1524 mm) above the adjoining walking surface.
Fire department hose connections	Attached to the face of the building, not more than 12 inches (305 mm) horizontally from the center line of the fire department hose connection, and not less than 42 inches (1067 mm) nor more than 60 inches (1524 mm) above the adjoining walking surface.

**DESIGNATION FOR STRUCTURAL COMPONENTS THAT ARE OF TRUSS CONSTRUCTION**